

Air and Multipurpose Hose



GST® II General Service Hose

Series 7031(R) (Green), Series 7057 (Blue), Series 7092 (Red), Series 7093 (Black), and Series 7096 (Yellow)



GST® II hose is a versatile general purpose hose designed to handle air, mild chemicals and water. The hose construction incorporates a tube that is compatible with light oil mists found in air tool lubricating systems, and the multiple plies of textile reinforcement provide flexibility. The cover is resistant to abrasion, heat and ozone, and is available in multiple standard colors for color-coded identification.

NOTE: Do not with use with oil or refined fuel.

Other cover colors available:

- 7031(R) (Green)
- 7096 (Yellow)

Series 7092 (Red)

Crimp Specifications
For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| -25200 | 1/4 | 6.4 | 2 | 0.5 | 12.7 | 0.09 | 0.13 | 3 | 64 | 200 | 14 | HY | 800 | Reel |
| -25300 | 1/4 | 6.4 | 2 | 0.6 | 14.0 | 0.12 | 0.18 | 3 | 84 | 300 | 21 | HY | 800 | Reel |
| -31300 | 5/16 | 7.9 | 2 | 0.6 | 15.9 | 0.14 | 0.21 | 4 | 89 | 300 | 21 | HY | 750 | Reel |
| -38200 | 3/8 | 9.5 | 2 | 0.7 | 16.7 | 0.14 | 0.21 | 4 | 89 | 200 | 14 | HY | 700 | Reel |
| -3820050 | | | | | | | | | | | | | 50 | Carton |

Factory Assemblies: Air, Service Station Air, Jackhammer and Sledgehammer hose assemblies are available from stock in popular configurations and appear at the end of this section.

⚠ WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

- Tube:** Black EPDM; ARPM Class C oil resistance
- Reinforcement:** Multiple textile plies
- Cover:** Black, blue, green, red, yellow EPDM; smooth finish
- Temp. Range:** -40°F to +212°F (-40°C to +100°C)
- Brand Method:** White ink on black, blue, green, red hose; black ink on yellow hose
- Brand Example:** PARKER (SERIES) GST® II (ID) XXX PSI MAX WP















- Design Factor:** 4:1
- Industry Standards:** ARPM IP-7 (7031R only)
- Applications:**
 - Air (including oil mist), mild chemicals, water
 - Agriculture, construction, general industrial
- Vacuum:** Not recommended
- Compare to:** Boston Bosflex A/W; ContiTech Frontier General Purpose; Gates Adapta Flex; Thermoid Valuflex GS

(Continued on the following page)

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

Series 7031(R), Series 7057, Series 7092, Series 7093, and Series 7096 – GST® II General Service Air & Water Hose (Continued)

Series 7092 (Red)

| # Part Number 7092 |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Min Bend Rad (in) |  Min Bend Rad (mm) |  Max WP (psi) |  Max WP (bar) |  Perm Cplg Rec * |  Nom Std Pack Qty (ft) |  Pkg Type |
|--------------------------|--|--|---|--|--|--|--|--|---|---|---|--|--|---|
| -38300 | 3/8 | 9.5 | 2 | 0.7 | 17.5 | 0.16 | 0.24 | 4 | 102 | 300 | 21 | HY | 700 | Reel |
| -3830050 | | | | | | | | | | | | HY | 50 | Carton |
| -50200 | 1/2 | 12.7 | 2 | 0.8 | 20.7 | 0.20 | 0.30 | 5 | 114 | 200 | 14 | HY | 550 | Reel |
| -50304 | 1/2 | 12.7 | 4 | 0.9 | 22.2 | 0.24 | 0.36 | 5 | 127 | 300 | 21 | HY | 500 | Reel |
| -5030450 | | | | | | | | | | | | HY | 50 | Carton |
| -63200 | 5/8 | 15.9 | 2 | 1.0 | 24.6 | 0.24 | 0.36 | 6 | 140 | 200 | 14 | HY | 450 | Reel |
| -6320050 | | | | | | | | | | | | HY | 50 | Carton |
| -63304 | 5/8 | 15.9 | 4 | 1.1 | 27.0 | 0.35 | 0.52 | 6 | 140 | 300 | 21 | HY | 450 | Reel |
| -75200 | 3/4 | 19.1 | 2 | 1.1 | 28.2 | 0.32 | 0.48 | 6 | 152 | 200 | 14 | HY | 400 | Reel |
| -7520050 | | | | | | | | | | | | HY | 50 | Carton |
| -75254 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 250 | 17 | HY | 400 | Reel |
| -7525450 | | | | | | | | | | | | HY | 50 | Carton |
| -75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 300 | 21 | HY | 400 | Reel |
| -7530450 | | | | | | | | | | | | HY | 50 | Carton |
| -100200 | 1 | 25.4 | 2 | 1.4 | 35.7 | 0.47 | 0.70 | 7 | 178 | 200 | 14 | HY | 300 | Reel |
| -100304 | 1 | 25.4 | 4 | 1.4 | 36.5 | 0.51 | 0.76 | 8 | 203 | 300 | 21 | HY | 300 | Reel |
| -125204 | 1-1/4 | 31.8 | 4 | 1.8 | 45.2 | 0.77 | 1.15 | 9 | 229 | 200 | 14 | HY | 250 | Reel |
| -150204 | 1-1/2 | 38.1 | 4 | 2.0 | 51.6 | 0.84 | 1.25 | 10 | 254 | 200 | 14 | 43 | 200 | Reel |
| -15020450 | | | | | | | | | | | | 43 | 50 | Carton |
| -150204100 | | | | | | | | | | | | 43 | 100 | Reel |
| -200154 | 2 | 50.8 | 4 | 2.6 | 64.8 | 1.13 | 1.68 | 14 | 356 | 200 | 14 | 43 | 250 | Reel |

Factory Assemblies: Air, Service Station Air, Jackhammer and Sledgehammer hose assemblies are available from stock in popular configurations and appear at the end of this section.

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

(Continued on the following page)

GST® II General Service Hose



Series 7031(R) (Green),
Series 7057 (Blue), Series 7092 (Red),
Series 7093 (Black), and Series 7096 (Yellow)

GST® II hose is a versatile general purpose hose designed to handle air, mild chemicals and water. The hose construction incorporates a tube that is compatible with light oil mists found in air tool lubricating systems, and the multiple plies of textile reinforcement provide flexibility. The cover is resistant to abrasion, heat and ozone, and is available in multiple standard colors for color-coded identification.

NOTE: Do not with use with oil or refined fuel.

Other cover colors available:

| | |
|-----------------|---|
| 7031(R) (Green) |  |
| 7057 (Blue) |  |
| 7096 (Yellow) |  |

Series 7093 (Black)

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| -19200 | 3/16 | 4.8 | 2 | 0.4 | 11.1 | 0.07 | 0.10 | 2 | 51 | 200 | 14 | * | 800 | Reel |
| -25200 | 1/4 | 6.4 | 2 | 0.5 | 12.7 | 0.09 | 0.13 | 3 | 64 | 200 | 14 | HY | 800 | Reel |
| -25250 | 1/4 | 6.4 | 2 | 0.5 | 12.9 | 0.10 | 0.15 | 3 | 76 | 250 | 17 | HY | 800 | Reel |
| -25300 | 1/4 | 6.4 | 2 | 0.6 | 14.0 | 0.12 | 0.18 | 3 | 84 | 300 | 21 | HY | 800 | Reel |

Factory Assemblies: Air, Service Station Air, Jackhammer and Sledgehammer hose assemblies are available from stock in popular configurations and appear at the end of this section.

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black EPDM; ARPM Class C oil resistance

Reinforcement: Multiple textile plies

Cover: Black, blue, green, red, yellow EPDM; smooth finish

Temp. Range: -40°F to +212°F (-40°C to +100°C)

Brand Method: White ink on black, blue, green, red hose;
black ink on yellow hose

Brand Example: PARKER (SERIES) GST® II (ID) XXX PSI
MAX WP

Design Factor: 4:1

Industry Standards: ARPM IP-7 (7031R only)

Applications:

- Air (including oil mist), mild chemicals, water
- Agriculture, construction, general industrial

Vacuum: Not recommended

Compare to: Boston Bosflex A/W; ContiTech
FrontierGeneral Purpose; Gates Adapta Flex;
Thermoid Valuflex GS

(Continued on the following page)

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

Series 7031(R), Series 7057, Series 7092, Series 7093, and Series 7096 – GST® II General Service Air & Water Hose (Continued)

Series 7093 (Black) (Continued)

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| -31200 | 5/16 | 7.9 | 2 | 0.6 | 15.1 | 0.12 | 0.18 | 3 | 84 | 200 | 14 | HY | 750 | Reel |
| -31300 | 5/16 | 7.9 | 2 | 0.6 | 15.9 | 0.14 | 0.21 | 4 | 89 | 300 | 21 | HY | 750 | Reel |
| -38200 | 3/8 | 9.5 | 2 | 0.7 | 16.7 | 0.14 | 0.21 | 4 | 89 | 200 | 14 | HY | 700 | Reel |
| -38300 | 3/8 | 9.5 | 2 | 0.7 | 17.5 | 0.16 | 0.24 | 4 | 102 | 300 | 21 | HY | 700 | Reel |
| -50200 | 1/2 | 12.7 | 2 | 0.8 | 20.7 | 0.20 | 0.30 | 5 | 114 | 200 | 14 | HY | 550 | Reel |
| -50250 | 1/2 | 12.7 | 2 | 0.8 | 21.4 | 0.22 | 0.33 | 5 | 114 | 250 | 17 | HY | 550 | Reel |
| -50304 | 1/2 | 12.7 | 4 | 0.9 | 22.2 | 0.24 | 0.36 | 5 | 127 | 300 | 21 | HY | 500 | Reel |
| -63200 | 5/8 | 15.9 | 2 | 1.0 | 24.6 | 0.24 | 0.36 | 6 | 140 | 200 | 14 | HY | 450 | Reel |
| -63304 | 5/8 | 15.9 | 4 | 1.1 | 27.0 | 0.35 | 0.52 | 6 | 140 | 300 | 21 | HY | 450 | Reel |
| -75200 | 3/4 | 19.1 | 2 | 1.1 | 28.2 | 0.32 | 0.48 | 6 | 152 | 200 | 14 | HY | 400 | Reel |
| -7520050 | | | | | | | | | | | | HY | 50 | Carton |
| -75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 300 | 21 | HY | 400 | Reel |
| -100200 | 1 | 25.4 | 2 | 1.4 | 35.7 | 0.47 | 0.70 | 7 | 178 | 200 | 14 | HY | 300 | Reel |
| -100304 | 1 | 25.4 | 4 | 1.4 | 36.5 | 0.51 | 0.76 | 8 | 203 | 300 | 21 | HY | 300 | Reel |
| -125204 | 1-1/4 | 31.8 | 4 | 1.8 | 45.2 | 0.77 | 1.15 | 9 | 229 | 200 | 14 | HY | 250 | Reel |
| -150204 | 1-1/2 | 38.1 | 4 | 2.0 | 51.6 | 0.84 | 1.25 | 10 | 254 | 200 | 14 | 43 | 200 | Reel |
| -200154 | 2 | 50.8 | 4 | 2.6 | 64.8 | 1.13 | 1.68 | 14 | 356 | 200 | 14 | 43 | 250 | Reel |

Factory Assemblies: Air, Service Station Air, Jackhammer and Sledgehammer hose assemblies are available from stock in popular configurations and appear at the end of this section.

Series 7031 / 7031(R) (Green)

7031R meets ARPM IP-7 requirements for Grade R oxygen service in welding applications.

Brand Example: PARKER 7031 GST® II/OXYGEN 3/4 ID (19.1mm) MAX WP 300 PSI (200 PSI OXYGEN) ARPM IP-7-2008 STD DUTY GRADE R



Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| 7031-75304R | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 300† | 21† | HY | 400 | Reel |
| 7031-7530450R | | | | | | | | | | | | HY | 50 | Carton |

† 200 psi (13.8 bar) maximum recommended working pressure for oxygen service.

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Series 7031(R), Series 7057, Series 7092, Series 7093, and Series 7096 – GST® II General Service Air & Water Hose (Continued)

Series 7057 (Blue)

| Crimp Specifications | | | | | | | | | | | | | | |
|---|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource . | | | | | | | | | | | | | | |
| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
| 7057-50250 | 1/2 | 12.7 | 2 | 0.8 | 21.4 | 0.23 | 0.34 | 5 | 114 | 250 | 17 | HY | 500 | Reel |
| 7057-75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 300 | 21 | HY | 350 | Reel |
| 7057-7530450 | | | | | | | | | | | | HY | 50 | Carton |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.



Series 7096 (Yellow)

| Crimp Specifications | | | | | | | | | | | | | | |
|---|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource . | | | | | | | | | | | | | | |
| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
| 7096-75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 300 | 21 | HY | 400 | Reel |
| 7096-7530450 | | | | | | | | | | | | HY | 50 | Carton |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

SUPER-FLEX® GS General Service Air & Water Hose

Series 7322 (Red) and
Series 7323 (Black)



Series 7322/7323 is a versatile general purpose hose designed to handle air, mild chemicals and water. The hose incorporates a tube that is compatible with light oil mists, and features a rigid mandrel construction that produces a **true** round, concentric profile for superior coupling fit and retention. The cover is resistant to abrasion, heat and ozone.

NOTE: Do not with use with oil or refined fuel.

Series 7322 (Red) and Series 7323 (Black)

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number 7322 or 7323 | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|-------------------------------------|------------|------------|-----------------|------------|------------|--------------------------|------------------------|----------------------------|----------------------------|--------------------|--------------------|--------------------------|--------------------------------|-------------|
| -125200 | 1-1/4 | 31.8 | 2 | 1.7 | 44.2 | 0.71 | 1.06 | 8 | 191 | 200 | 14 | 43 | 200 | Coil |
| -150200 | 1-1/2 | 38.1 | 2 | 2.0 | 50.4 | 0.82 | 1.22 | 9 | 216 | 200 | 14 | 43 | 200 | Coil |
| -200200 | 2 | 50.8 | 4 | 2.6 | 65.2 | 1.23 | 1.83 | 12 | 305 | 200 | 14 | 43 | 200 | Coil |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black EPDM; ARPM Class C oil resistance

Reinforcement: Multiple textile plies

Cover: 7322: Red EPDM, wrapped finish
7323: Black EPDM, wrapped finish

Temp. Range: -40°F to +212°F (-40°C to +100°C)

Brand Method: 7322: White text on red stripe
7323: White text on black stripe

Brand Example: PARKER SERIES (7322) (7323) SUPER-FLEX® GS 200 PSI MAX WP GENERAL SERVICE

Design Factor: 4:1

Vacuum: Not recommended

Industry Standards: None applicable

Applications:

- Air (including oil mist), mild chemicals, water
- Agriculture, construction, general industrial

Compare to: ContiTech Frontier; Gates AdaptaFlex

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

MPT® II Multipurpose Oil Resistant Hose

Series 7094 (Red) and
Series 7095 (Black)














Series 7094/7095 hose construction is electrically nonconductive multipurpose hose with a minimum resistance of one megaohm per inch at 1000 volts DC. The multiple plies of textile reinforcement provide flexibility and the cover is resistant to oil and weathering.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube of the hose to lubricating oil mist from the compressor).
 - The user must determine if the hose is suitable for applications subject to electrical hazard. Contact Parker for additional information.
 - Do not use to dispense or transfer biodiesel, diesel fuel, or gasoline.

Series 7094 (Red)

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # |  |  |  |  |  |  |  |  |  |  |  | | | |
|------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Part Number 7094 | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
| -25200 | 1/4 | 6.4 | 2 | 0.5 | 12.7 | 0.10 | 0.15 | 2 | 51 | 200 | 14 | HY | 800 | Reel |
| -25300 | | | | 0.6 | 14.0 | 0.12 | 0.18 | 3 | 64 | 300 | 21 | HY | 800 | Reel |
| -31300 | 5/16 | 7.9 | 2 | 0.6 | 15.1 | 0.13 | 0.19 | 3 | 84 | 300 | 21 | HY | 750 | Reel |
| -38200 | 3/8 | 9.5 | 2 | 0.7 | 16.7 | 0.15 | 0.22 | 4 | 97 | 200 | 14 | HY | 700 | Reel |
| -38300 | 3/8 | 9.5 | 2 | 0.7 | 17.5 | 0.17 | 0.25 | 4 | 97 | 300 | 21 | HY | 650 | Reel |
| -50200 | 1/2 | 12.7 | 2 | 0.8 | 20.7 | 0.21 | 0.31 | 5 | 127 | 200 | 14 | HY | 550 | Reel |
| -50304 | 1/2 | 12.7 | 4 | 0.9 | 22.2 | 0.26 | 0.39 | 5 | 127 | 300 | 21 | HY | 500 | Reel |
| -63304 | 5/8 | 15.9 | 4 | 1.1 | 27.0 | 0.38 | 0.57 | 6 | 155 | 300 | 21 | HY | 450 | Reel |
| -75200 | 3/4 | 19.1 | 2 | 1.1 | 28.2 | 0.34 | 0.51 | 8 | 191 | 200 | 14 | HY | 400 | Reel |
| -75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.40 | 0.60 | 6 | 152 | 300 | 21 | HY | 400 | Reel |
| -100200 | 1 | 25.4 | 2 | 1.4 | 35.7 | 0.49 | 0.73 | 10 | 254 | 200 | 14 | HY | 300 | Reel |
| -100304 | | | | 1.4 | 36.5 | 0.54 | 0.80 | 8 | 203 | 300 | 21 | HY | 300 | Reel |
| -125204 | 1-1/4 | 31.8 | 4 | 1.8 | 45.2 | 0.82 | 1.22 | 9 | 229 | 200 | 14 | HY | 250 | Reel |
| -150204 | 1-1/2 | 38.1 | 4 | 2.0 | 51.6 | 0.90 | 1.34 | 10 | 254 | 200 | 14 | HY | 200 | Reel |

WARNING: This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

(Continued on the following page)













WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

Series 7094 (Red) and Series 7095 (Black) – MPT® II Multipurpose Oil Resistant Hose – Nonconductive (Continued)

Series 7095 (Black)

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Min Bend Rad (in) |  Min Bend Rad (mm) |  Max WP (psi) |  Max WP (bar) |  Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---|---|--|---|---|--|---|---|---|--|--|---|---|--|
| -25300 | | | | 0.6 | 14.0 | 0.12 | 0.18 | 3 | 64 | 300 | 21 | HY | 800 | Reel |
| -31300 | 5/16 | 7.9 | 2 | 0.6 | 15.1 | 0.13 | 0.19 | 3 | 84 | 300 | 21 | HY | 750 | Reel |
| -38200 | 3/8 | 9.5 | 2 | 0.7 | 16.7 | 0.15 | 0.22 | 4 | 97 | 200 | 14 | HY | 700 | Reel |
| -38300 | 3/8 | 9.5 | 2 | 0.7 | 17.5 | 0.17 | 0.25 | 4 | 97 | 300 | 21 | HY | 650 | Reel |
| -50200 | 1/2 | 12.7 | 2 | 0.8 | 20.7 | 0.21 | 0.31 | 5 | 127 | 200 | 14 | HY | 550 | Reel |
| -50304 | 1/2 | 12.7 | 4 | 0.9 | 22.2 | 0.26 | 0.39 | 5 | 127 | 300 | 21 | HY | 500 | Reel |
| -63304 | 5/8 | 15.9 | 4 | 1.1 | 27.0 | 0.38 | 0.57 | 6 | 155 | 300 | 21 | HY | 450 | Reel |
| -75200 | 3/4 | 19.1 | 2 | 1.1 | 28.2 | 0.34 | 0.51 | 8 | 191 | 200 | 14 | HY | 400 | Reel |
| -75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.40 | 0.60 | 6 | 152 | 300 | 21 | HY | 400 | Reel |
| -100304 | 1 | 25.4 | 2 | 1.4 | 36.5 | 0.54 | 0.80 | 8 | 203 | 300 | 21 | HY | 300 | Reel |
| -125204 | 1-1/4 | 31.8 | 4 | 1.8 | 45.2 | 0.82 | 1.22 | 9 | 229 | 200 | 14 | HY | 250 | Reel |
| -150204 | 1-1/2 | 38.1 | 4 | 2.0 | 51.6 | 0.90 | 1.34 | 10 | 254 | 200 | 14 | HY | 200 | Reel |

WARNING: This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Tube: Black nitrile; ARPM Class A oil resistance

Reinforcement: Multiple textile plies

Cover: 7094: Red chloroprene, smooth finish

7095: Black chloroprene, smooth finish

Temp. Range: Air: -20°F to +158°F (-29°C to +70°C)

Other Media: -20°F to +212°F (-29°C to +100°C)

Brand Method: White ink

Brand Example: PARKER SERIES (7094) (7095) MPT® II (ID) XXX PSI MAX WP ELECTRICALLY NONCONDUCTIVE

Design Factor: 4:1

Industry Standards: Electrically nonconductive with a minimum resistance of one megaohm per inch at 1000 volts DC

Applications:

- Air, mild chemicals, oil, water
- Cooling lines for electric furnaces and pot lines; lubrication systems
- Agriculture, construction, foundries, general industrial

Vacuum: Not recommended

Compare to: Boston Shock Safe; ContiTech Ortac/Variflex; Gates PremoFlex/19B

SUPER MPT® II

Multipurpose Oil Resistant Hose

Series 7396



Series 7396 is a versatile, nonconductive multipurpose hose designed to handle air, mild chemicals, oil and water. The hose is electrically nonconductive with a minimum resistance of one megaohm per inch at 1000 volts DC. The rigid mandrel construction produces a *true* round, concentric profile for superior coupling fit and retention. The cover is resistant to oil and weathering.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube of the hose to lubricating oil mist from the compressor).
 - The user must determine if the hose is suitable for applications subject to electrical hazard. Contact Parker for additional information.
 - Do not use to dispense or transfer biodiesel, diesel fuel or gasoline in regulated service (API, NFPA, UL, ULC or any other agency approval or listing).
 - Do not use in vehicle engine applications.
 - Refer to the Refined Fuel/Hose Compatibility Table in the Media Compatibility section.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| 7396-125300200 | 1-1/4 | 31.8 | 4 | 1.8 | 45.7 | 0.79 | 1.18 | 8 | 191 | 300 | 21 | * | 200 | Coil |
| 7396-150300200 | 1-1/2 | 38.1 | 4 | 2.0 | 51.4 | 0.87 | 1.30 | 9 | 216 | 300 | 21 | * | 200 | Coil |
| 7396-200300200 | 2 | 50.8 | 4 | 2.6 | 66.0 | 1.29 | 1.92 | 12 | 305 | 300 | 21 | * | 200 | Coil |

WARNING: This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Tube: Black nitrile; ARPM Class A oil resistance

Reinforcement: Multiple textile plies

Cover: Red chloroprene, wrapped finish

Temp. Range: Air: -20°F to +158°F (-29°C to +70°C)

Other Media: -20°F to +212°F (-29°C to +100°C)

Brand Method: White text on red stripe

Brand Example: PARKER SERIES 7396 SUPER-MPT®
MULTIPURPOSE HOSE XXX PSI MAX WP
ELECTRICALLY NONCONDUCTIVE

Design Factor: 4:1

Industry Standards: Electrically nonconductive with a minimum resistance of one megaohm per inch at 1000 volts DC

Applications:

- Air, mild chemicals, oil, water
- Cooling lines for electric furnaces and pot lines; lubrication systems
- Agriculture, construction, foundries, general industrial

Vacuum: Not recommended

Compare to: ContiTech Ortac 250; Gates Duroflex

⚠️ WARNINGS!

- ▶ Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.
- ▶ The hose does not incorporate a helical wire; transfer of refined fuel may create an accumulation – and catastrophic discharge – of static electrical buildup.

JIFFY™ Push-On Multipurpose Hose Series 7212



Series 7212 hose construction incorporates a silicone-free tube that does not contaminate air powered paint spray systems. The braided textile reinforcement is applied at a precise angle to provide kink resistance and superior coupling retention—to be used with push-on couplings which do not require bands, clamps or special tools for installation. The flame resistant cover meets MSHA requirements and is resistant to oil and weathering.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube to a lubricating oil mist).
 - Do not use to dispense or transfer biodiesel, diesel fuel, or gasoline in regulated service (API, NFPA, UL, ULC or any other agency approval or listing).
 - Do not use in vehicle engine applications.
 - Refer to the Refined Fuel/Hose Compatibility Table in the Media Compatibility section.
 - Do not use bands or clamps to attach push-on couplings.

Other colors available:

- 7212-BL
- 7212-GN
- 7212-GY
- 7212-RD
- 7212-YL

⚠ WARNING!

► The hose does not include a static wire; transfer of refined fuel may create an accumulation – and catastrophic discharge – of static electrical buildup.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | | | | | | | | | | | | | | |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
| 7212-251XX | 1/4 | 6.4 | 1 | 0.5 | 12.5 | 0.09 | 0.13 | 3 | 76 | 300 | 21 | HY | 700 | Reel |
| 7212-381XX | 3/8 | 9.5 | 1 | 0.6 | 15.7 | 0.12 | 0.18 | 3 | 76 | 300 | 21 | HY | 700 | Reel |
| 7212-501XX | 1/2 | 12.7 | 1 | 0.8 | 19.1 | 0.15 | 0.22 | 5 | 127 | 300 | 21 | HY | 600 | Reel |
| 7212-631XX | 5/8 | 15.9 | 1 | 0.9 | 23.0 | 0.21 | 0.31 | 6 | 152 | 300 | 21 | HY | 500 | Reel |
| 7212-750XX | 3/4 | 19.1 | 1 | 1.1 | 27.7 | 0.30 | 0.45 | 7 | 178 | 300 | 21 | HY | 400 | Reel |

XX in Part Number = BK (black), BL (blue), GN (green), GY (grey), RD (red), YL (yellow)

Factory Cut Lengths: Blue and gray hose available from stock in 50-ft. coils. See the following page.

Reattachable Couplings: Parker Series 82 Push-Lok® couplings.

⚠ WARNING: This product can expose you to chemicals including 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Tube: Black nitrile; ARPM Class A oil resistance

Reinforcement: One textile braid

Cover: Black, blue, gray, green, red or yellow chloroprene; smooth finish

Temp. Range: Air: -40°F to +158°F (-40°C to +70°C)

Other Media: -40°F to +212°F (-40°C to +100°C)

Brand Method: White ink on black, blue and red hose; black ink on green, gray and yellow hose

Brand Example: PARKER 7212 JIFFY™ HOSE PUSH-ON (ID) 300 PSI MAX WP MSHA #

Design Factor: 4:1

Industry Standards: MSHA

Applications:

- Air, mild chemicals, oil, water; biodiesel (to B20 in dedicated service), diesel, ethanol, gasoline
- Air operated paint systems, air tools, transfer lines, vacuum lines
- Agriculture, construction, general industrial; automotive/factory color-coded assembly equipment

Compare to: ContiTech Autogrip; Gates Python Plus; Thermoid Flex Loc 300

Vacuum: 1/4" ID through 1/2" ID @ 28" Hg (711 mm Hg); 5/8" ID through 3/4" ID @ 15" Hg (381 mm Hg)

GRIZZLY™ 500 Multipurpose Hose

Series 7107

















Series 7107 hose is multipurpose hose that is electrically nonconductive with a minimum resistance of one megaohm per inch at 1000 volts DC. The bright yellow flame resistant modified nitrile/PVC cover is resistant to abrasion, oil and weathering.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube to a lubricating oil mist).
 - The user must determine if the hose is suitable for applications subject to electrical hazard. Review the safety guide for electrical resistance.
 - Do not use to dispense or transfer biodiesel, diesel fuel, or gasoline.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Min Bend Rad (in) |  Min Bend Rad (mm) |  Max WP (psi) |  Max WP (bar) |  Perm Cplg Rec * |  Nom Std Pack Qty (ft) |  Pkg Type |
|------------------|---|---|--|---|---|--|--|---|--|--|--|---|---|--|
| 7107-25500 | 1/4 | 6.4 | 4 | 0.6 | 15.9 | 0.16 | 0.24 | 2 | 51 | 500 | 34 | * | 750 | Reel |
| 7107-38500 | 3/8 | 9.5 | 4 | 0.8 | 19.1 | 0.20 | 0.30 | 3 | 76 | 500 | 34 | HY | 600 | Reel |
| 7107-50500 | 1/2 | 12.7 | 4 | 0.9 | 22.2 | 0.27 | 0.40 | 3 | 76 | 500 | 34 | * | 500 | Reel |
| 7107-75500 | 3/4 | 19.1 | 4 | 1.2 | 30.1 | 0.40 | 0.60 | 5 | 127 | 500 | 34 | HY | 400 | Reel |
| 7107-75500050 | | | | | | | | | | | | HY | 24 x 50 | Carton |
| 7107-100500 | 1 | 25.4 | 4 | 1.5 | 38.1 | 0.59 | 0.88 | 6 | 152 | 500 | 34 | * | 300 | Reel |
| 7107-125500 | 1-1/4 | 31.8 | 4 | 1.8 | 45.7 | 0.80 | 1.19 | 9 | 229 | 500 | 34 | 43 | 250 | Reel |
| 7107-150500 | 1-1/2 | 38.1 | 4 | 2.0 | 51.6 | 0.91 | 1.36 | 12 | 305 | 500 | 34 | 43 | 200 | Reel |
| 7107-200500 | 2 | 50.8 | 4 | 2.685 | 68.2 | 1.31 | 1.95 | 24.0 | 609.6 | 500 | 34 | * | 100 | Coil |

WARNING: This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Tube: Black nitrile; ARPM Class A oil resistance

Reinforcement: Multiple aramid plies; 2" ID (only) multiple textile plies

Cover: Yellow nitrile/PVC, smooth finish; 2" ID (only) wrapped finish

Temp. Range: Air: -40°F to +158°F (-40°C to +70°C)

Other Media: -40°F to +212°F (-40°C to +100°C)

Brand Method: Black ink

Brand Example: PARKER SERIES 7107 GRIZZLY (ID)
500 PSI MAX WP ELECTRICALLY
NONCONDUCTIVE MSHA #

Design Factor: 4:1

Industry Standards: Electrically nonconductive with a minimum resistance of one megaohm per inch at 1000 volts DC; MSHA

Applications:

- Air, oil, mild chemicals, water
- Agriculture, construction, foundries, general industrial, mines

Vacuum: Not recommended

Compare to: Boston Mineforce; ContiTech Gorilla; Gates Terminator

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

ARCTIC EDGE™ Low Temperature Multipurpose Hose



Series 7102

Series 7102 hose construction is a low temperature multipurpose hose that incorporates a static wire as a path to conduct an electrical charge to ground. The multiple plies of textile reinforcement provide flexibility and kink resistance to -70°F (-57°C). The cover is resistant to oil and weathering, and incorporates a longitudinal solid blue stripe for color-coded identification.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube to a lubricating oil mist).
 - Do not use to dispense or transfer biodiesel, diesel fuel, or gasoline in regulated service (API, NFPA, UL, ULC or any other agency approval or listing).
 - Do not use in vehicle engine applications.
 - Refer to the Refined Fuel/Hose Compatibility Table in the Media Compatibility section.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| 7102-38304 | 3/8 | 9.5 | 4 | 0.8 | 19.1 | 0.21 | 0.31 | 4 | 97 | 300 | 21 | HY | 650 | Reel |
| 7102-50304 | 1/2 | 12.7 | 4 | 0.9 | 23.0 | 0.28 | 0.42 | 5 | 127 | 300 | 21 | * | 500 | Reel |
| 7102-75304 | 3/4 | 19.1 | 4 | 1.2 | 29.4 | 0.37 | 0.55 | 6 | 152 | 300 | 21 | HY | 400 | Reel |
| 7102-100304 | 1 | 25.4 | 4 | 1.5 | 37.0 | 0.54 | 0.80 | 8 | 203 | 300 | 21 | HY | 300 | Reel |
| 7102-125304 | 1-1/4 | 31.8 | 4 | 1.8 | 46.0 | 0.83 | 1.24 | 9 | 229 | 300 | 21 | HY | 250 | Reel |
| 7102-138304 | 1-3/8 | 34.9 | 4 | 1.9 | 48.9 | 0.89 | 1.33 | 10 | 241 | 300 | 21 | * | 200 | Reel |

⚠ WARNING: This product can expose you to chemicals including DEHP, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Tube: Black nitrile; ARPM Class A oil resistance
Reinforcement: Multiple textile plies with static wire
Cover: Black chloroprene; smooth finish
Temp. Range: Air: -70°F to +158°F (-57°C to +70°C)
Other Media: -70°F to +212°F (-57°C to +100°C)
Brand Method: White ink; solid blue stripe on reverse
Brand Example: PARKER SERIES 7102 ARCTIC EDGE™
 (-70°F) LOW TEMP (ID) 300 PSI MAX WP
Design Factor: 4:1

Industry Standards: None applicable
Applications:

- Air, mild chemicals, oil, water; biodiesel (to B20 in dedicated service), diesel, ethanol, gasoline
- Cold weather, refrigerated applications
- Agriculture, construction, general industrial

Vacuum: Not recommended
Compare to: ContiTech Arctic Ortac; Thermoid Glacier Multipurpose

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

DAY-FLO® Multipurpose Oil Resistant Hose

Series 7187



Series 7187 is a versatile, multipurpose hose. The braided textile reinforcement provides kink resistance and superior coupling retention, and the cover is resistant to oil and weathering.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube of the hose to lubricating oil mist from the compressor).
 - Do not use to dispense or transfer biodiesel, diesel fuel, or gasoline

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number 7187 | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|--------------------------|------------|------------|-----------------|------------|------------|--------------------------|------------------------|----------------------------|----------------------------|-----------------|-----------------|--------------------------|--------------------------------|-------------|
| 7187-191 | 1/2 | 12.7 | 2 | 0.9 | 22.2 | 0.26 | 0.39 | 5 | 122 | 300 | 21 | HY | 600 | Reel |
| 7187-251 | 1/4 | 6.4 | 1 | 0.5 | 12.7 | 0.09 | 0.13 | 3 | 64 | 250 | 17 | HY | 700 | Reel |
| 7187-252 | | | 2 | 0.6 | 15.1 | 0.15 | 0.22 | 3 | 84 | 300 | 21 | HY | 700 | Reel |
| 7187-382 | 3/8 | 9.5 | 2 | 0.7 | 18.3 | 0.19 | 0.28 | 4 | 102 | 300 | 21 | HY | 700 | Reel |

Tube: Black nitrile; ARPM Class A oil resistance

Reinforcement: One or multiple textile braids

Cover: 7187: Black chloroprene, smooth finish

Temp. Range: Air: -20°F to +158°F (-29°C to +70°C)

Other Media: -20°F to +212°F (-29°C to +100°C)

Brand Method: White ink

Brand Example: PARKER SERIES (7187) DAY-FLO® (ID)
XXX PSI MAX WP

Design Factor: 4:1

Industry Standards: None applicable

Applications:

- Air, mild chemicals, oil, water
- Agriculture, construction, general industrial

Vacuum: Not recommended

Compare to: Boston Easy Couple

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

WHIPPET® 200

Multipurpose Hose

Series 7137



Series 7137 multipurpose hose has a braided textile reinforcement that provides kink resistance and superior coupling retention, and the cover is resistant to oil and weathering.

- NOTES:**
- Do not use in dry air applications (typically, air systems that do not expose the tube of the hose to lubricating oil mist from the compressor).
 - Do not use to dispense or transfer biodiesel, diesel fuel, or gasoline.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| 7137-251 | 1/4 | 6.4 | 1 | 0.4 | 11.0 | 0.06 | 0.09 | 2 | 51 | 200 | 14 | HY | 700 | Reel |
| 7137-311 | 5/16 | 7.9 | 1 | 0.5 | 13.5 | 0.09 | 0.13 | 3 | 64 | 200 | 14 | HY | 700 | Reel |

WARNING: This product can expose you to chemicals including 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Tube: Black nitrile; ARPM Class A oil resistance
Reinforcement: One textile braid
Cover: Black chloroprene; smooth finish
Temp. Range: Air: -40°F to +158°F (-40°C to +70°C)
Other Media: -40°F to +212°F (-40°C to +100°C)
Brand Method: Not branded
Design Factor: 4:1

Industry Standards: None applicable
Applications:

- Air, mild chemicals, oil, water
- Air tools, hose whips
- Assembly lines, general industrial

Vacuum: Not recommended
Compare to: Boston Easy Couple

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

MAXIFLEX® Lightweight Air Hose













Series 7308E



Series 7308E is a flexible, lightweight, medium pressure hose designed to handle air, including light oil lubricating mists found in air tool lubricating systems, mild chemicals and water. The rugged cover is resistant to abrasion and weathering. Series 7308E provides service for low to medium pressure air and water applications in construction, general industrial, mines and quarries.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Max WP (psi) |  Max WP (bar) |  Perm Cplg Rec * |  Nom Std Pack Qty (ft) |  Pkg Type |
|------------------|---|---|--|---|---|--|--|--|--|---|---|--|
| 7308E-2000 | 2 | 50.8 | 4 | 2.6 | 66.0 | 1.16 | 1.73 | 300 | 21 | * | 100 | Coil |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black SBR

Reinforcement: Multiple textile plies

Cover: Yellow SBR; wrapped finish

Temp. Range: -20°F to +212°F (-29°C to +100°C)

Brand Method: Embossed

Brand Example: PARKER SERIES 7308E MAXIFLEX AIR HOSE 300 PSI WP

Design Factor: 3:1

Industry Standards: None applicable

Applications:

- Air, water
- Heavy duty air tools, compressors
- Construction, general industrial, mines, quarries

Vacuum: Not recommended

Compare to: ContiTech Plicord Air 300

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

DRAGON BREATH® Hot Air Blower Hose















Series SW360



Series SW360 hose transfers hot air from a truck's compressor to the storage bin/cargo bay to blow out bulk material. The hose offers full suction capability, kink resistance, flexibility for ease of handling and a path to conduct a static electrical charge to ground. The cover resists abrasion, heat and ozone.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Min Bend Rad (in) |  Min Bend Rad (mm) |  Max WP (psi) |  Max WP (bar) |  Perm Cplg Rec * |  Nom Std Pack Qty (ft) |  Pkg Type |
|------------------|---|---|--|---|---|--|--|---|---|--|--|---|---|--|
| SW360-1500 | 1-1/2 | 38.1 | 2 | 2.0 | 51.0 | 1.06 | 1.58 | 5 | 127 | 200 | 14 | * | 100 | Coil |
| SW360-2000 | 2 | 50.8 | 2 | 2.5 | 64.7 | 1.52 | 2.26 | 6 | 152 | 200 | 14 | * | 100 | Coil |
| SW360-3000 | 3 | 76.2 | 2 | 3.6 | 90.9 | 2.54 | 3.78 | 12 | 305 | 200 | 14 | * | 100 | Coil |
| SW360-4000 | 4 | 101.6 | 2 | 4.6 | 116.6 | 3.73 | 5.55 | 16 | 406 | 125 | 9 | * | 100 | Coil |
| SW360-6000 | 6 | 152.4 | 2 | 6.7 | 169.4 | 4.65 | 6.92 | 24 | 610 | 100 | 7 | * | 100 | Coil |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black EPDM

Reinforcement: Multiple textile plies with single or dual wire helix

Cover: Black EPDM; wrapped finish

Temp. Range: -40°F to +350°F (-40°C to +177°C)

Brand Method: Black text on yellow stripe

Brand Example: PARKER DRAGON BREATH SW360 HOT AIR BLOWER HOSE XXX PSI WP

Design Factor: 4:1

Industry Standards: None applicable

Applications:

- Hot air blower systems
- In-plant transfer; delivery, loading/unloading
- General industrial, transportation

Compare to: ContiTech Plicord Torrid Air; Eaton Boston Wildcat Hot Air; Gates Hot Air Blower

Vacuum: 29" Hg (737 mm Hg)

⚠️ WARNINGS!

- ▶ Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.
- ▶ Do not use with cam and groove couplings, which are designed for use with liquids.

THORO-BRAID® Medium Pressure Wire Braid Multipurpose Hose

Series 7251



Series 7251 hose construction incorporates high tensile wire braid reinforcement that provides durability, kink resistance, medium pressure capability, and superior coupling retention. The flame resistant yellow cover is resistant to abrasion and oil.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| 7251-1501K | 1-1/2 | 38.1 | 1 | 2.1 | 52.4 | 1.22 | 1.82 | 20 | 508 | 600 | 41 | 43, 71 | 150 | Carton |
| 7251-2002K | 2 | 50.8 | 2 | 2.7 | 67.5 | 1.89 | 2.82 | 25 | 635 | 600 | 41 | 43, * | 150 | Carton |
| 7251-2502K | 2-1/2 | 63.5 | 2 | 3.2 | 80.2 | 2.30 | 3.43 | 32 | 813 | 500 | 35 | * | 150 | Carton |
| 7251-3002K | 3 | 76.2 | 2 | 3.7 | 92.9 | 2.73 | 4.07 | 37 | 927 | 500 | 35 | * | 150 | Carton |
| 7251-4002K | 4 | 101.6 | 2 | 4.7 | 118.3 | 3.63 | 5.41 | 48 | 1219 | 400 | 28 | * | 150 | Coil |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black chloroprene

Reinforcement: One or multiple wire braids

Cover: Yellow nitrile/PVC; perforated wrapped finish

Temp. Range: -20°F to +212°F (-29°C to +100°C)

Brand Method: Embossed

Brand Example: PARKER SERIES 7251 THORO-BRAID®
AIR HOSE - WIRE BRAID XXX PSI MAX
WP-DE4 FIRE RESISTANT-MSHA #

Design Factor: 4:1

Industry Standards: MSHA

Applications:

- Air, mild chemicals, oil, water
- Heavy duty air tools, compressors; bull hose, drill hose
- Construction, general industrial, mines and quarries

Vacuum: Not recommended

Compare to: ContiTech Ultrabraid Steel Air; Gates 500 MP/
Air Drill; Kuriyama T130AK

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

YELLOW BIRD® High Pressure Wire Braid Mine and Multipurpose Hose

Series 7284



Series 7284 is a versatile, heavy duty high pressure hose commonly used in mining. The construction incorporates high tensile wire braid reinforcement that provides durability, kink resistance, high pressure capability, and superior coupling retention. The flame resistant bright yellow cover meets MSHA requirements and is also resistant to abrasion and oil.

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Min Bend Rad (in) | Min Bend Rad (mm) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Nom Std Pack Qty (ft) | Pkg Type |
|------------------|---------|---------|--------------|---------|---------|--------------------|------------------|-------------------|-------------------|--------------|--------------|-----------------|-----------------------|----------|
| 7284-381050 | 3/8 | 9.5 | 1 | 0.7 | 17.8 | 0.23 | 0.34 | 6 | 152 | 1500 | 103 | HY | 50 | Carton |
| 7284-501050 | 1/2 | 12.7 | 1 | 1.0 | 24.6 | 0.37 | 0.55 | 7 | 178 | 1000 | 69 | * | 50 | Carton |
| 7284-751050 | 3/4 | 19.1 | 1 | 1.2 | 31.0 | 0.50 | 0.75 | 10 | 241 | 1000 | 69 | HY | 50 | Carton |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black SBR

Reinforcement: One wire braid

Cover: Yellow nitrile/PVC; perforated wrapped finish

Temp. Range: -20°F to +212°F (-29°C to +100°C)

Brand Method: Black ink

Brand Example: PARKER SERIES 7284 YELLOW BIRD®
HOSE XXXX PSI MAX WP
MSHA #—FLAME RESISTANT

Design Factor: 4:1

Industry Standards: MSHA

Applications:

- Air, water
- Heavy duty air tools, compressors; drill hose, dust suppression in mines
- Construction, general industrial, mines and quarries

Vacuum: Not recommended

Compare to: Boston Concord Yellow Jack; Gates 1000MP/ Mine Spray; Thermoid Hercules 1000

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

Factory Assemblies

Air Hose

Series 7092 (Red) and Series 7093 (Black)

Series 7092/7093 factory-installed, crimped-on lightweight brass couplings provide a secure hose/fitting interface, and the rigid male NPT ends provide easy, quick and secure connections.



| # Part Number | ID | | Length | | Approx Wt | | Max WP | | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|------|------|--------|-------|-----------|---------|--------|-------|-----------------|-------------------|----------|
| | (in) | (mm) | (ft) | (m) | (lbs/ea) | (kg/ea) | (psi) | (bar) | | | |
| 7092253-KAA | 1/4 | 6.4 | 50 | 15.24 | 6.01 | 2.73 | 300 | 21 | * | 5 | Carton |
| 7092253-KAB | | | 25 | 7.62 | 3.15 | 1.43 | | | | | |
| 7092382-KAC | 3/8 | 9.5 | 50 | 15.24 | 7.37 | 3.34 | 200 | 14 | * | 5 | Carton |
| 7092383-KAA | | | 50 | 15.24 | 8.33 | 3.78 | | | | | |
| 7092383-KAB | 3/8 | 9.5 | 25 | 7.62 | 4.34 | 1.87 | 300 | 21 | * | 10 | Carton |

⚠ WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Series 7093 (Black)

| # Part Number | ID | | Length | | Approx Wt | | Max WP | | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|------|------|--------|-------|-----------|---------|--------|-------|-----------------|-------------------|----------|
| | (in) | (mm) | (ft) | (m) | (lbs/ea) | (kg/ea) | (psi) | (bar) | | | |
| 7093383-KAA | 3/8 | 9.5 | 50 | 15.24 | 8.09 | 3.67 | 300 | 21 | * | 5 | Carton |

⚠ WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Temp Range: -40°F to +160°F (-40°C to +100°C)

Design Factor: 4:1

Crimped-on Brass: Rigid Male 1/4" x 1/4" NPT Thread Couplings Each End

Display Cartons with Parker Center Retail Packaging Disc

Series 7092 (Red)










Factory Assemblies

Service Station Air Hose

Series 7092 (Red)



Series 7092 is designed as an abrasion and weather resistant hose for service station compressor and general industrial air service. The factory-installed, crimped-on lightweight brass couplings provide a secure hose/fitting interface, and the rigid male NPT ends provide easy, quick and secure connections.

| # Part Number |  ID (in) |  Length (ft) |  Approx Wt (lbs/ea) |  Approx Wt (kg/ea) |  Max WP (psi) |  Cplg Thread Size (in) |  Perm Cplg Rec * |  Std Pack Qty (ea) |  Pkg Type |
|------------------|---|---|--|---|--|---|---|---|--|
| 7092RLC-300 | 3/8 | 25 | 4.34 | 1.97 | 300 | 1/4 x 1/4 | * | 10 | Carton |
| 7092RLC-600 | | 50 | 8.33 | 3.78 | | | * | 5 | Carton |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Temp Range: -40°F to +212°F (-40°C to +100°C)

Design Factor: 4:1

Crimped-on Brass: Rigid Male NPT Thread Couplings Each End

Cartoned and Tied: No Center Disc

Carton

TWINHAMMER™ Air / Water Jackhammer Hose System

Series 7084



The Parker jackhammer hose spray kit provides an engineered transfer of water from the supply hose to the jackhammer bit. The kit is easy to install and provides consistent water angle, distance, flow and spray pattern for effective silica dust control. The kit can be used as part of an OSHA-compliant wet method hose system for silica dust suppression. The kit includes the hardware and attachment components to apply to many models and generations of jackhammers*:

- Couplings/connectors • Straps • Water nozzle • Jumper hose • Thread tape
- Installation instructions • Shims • Water valve

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource.

| # Part Number | Hose Color | ID (in) | ID (mm) | Reinf Layers | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/m) | Length (ft/ea) | Length (m/ea) | Max WP (psi) | Max WP (bar) | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|------------|---------|---------|--------------|---------|---------|--------------------|------------------|----------------|---------------|--------------|--------------|-----------------|-------------------|----------|
| 7084JHT75-600 | Red | 3/4 | 19.1 | 2 | 1.16 | 29.4 | 26.7 | 39.78 | 50 | 15.2 | 300 | 21 | * | 1 | Carton |
| 7084JHT75-600B | Red | 3/4 | 19.1 | 2 | 1.16 | 29.4 | 26.7 | 39.78 | 50 | 15.2 | 300 | 21 | * | 15 | Carton |

Air hose is rated to 300 psi maximum working pressure. Finished hose assembly is rated to 150 psi due to limitation of the industry preferred fitting end style/connection.

WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

(Continued on the following page)

Tube: Black EPDM

Reinforcement: Multiple textile plies

Cover: Air Hose: Red EPDM

Water Hose: Blue EPDM

Temp. Range: -40°F to +212°F (-40°C to +100°C)

Brand Method: Air Hose: White ink

Water Hose: No brand

Brand Example: PARKER SERIES 7084 300 PSI MAX WP

Design Factor: 3:1

Industry Standards: None applicable

Applications:

- Wet method dust suppression hose system for pneumatic jackhammers

Vacuum: Not recommended

Couplings: Air Hose: Crimped carbon steel universal each end

Water Hose: Crimped brass 3/8" x 3/8" rigid male NPT each end

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

TWINHAMMER™ Air/Water Jackhammer Hose System

Series 7084

Jackhammer Hose Spray Kit

The Parker jackhammer hose spray kit provides an engineered transfer of water from the supply hose to the jackhammer bit. The kit is easy and convenient to install and provides efficient and consistent water angle, distance, flow and spray pattern for effective silica dust control. The kit can be used as part of an OSHA-compliant wet method hose system for silica dust suppression.



The kit includes the hardware and attachment components to apply to many models and generations of jackhammers*:

- Couplings/connectors
- Straps
- Water nozzle
- Jumper hose
- Thread tape
- Installation instructions
- Shims
- Water valve

Twinhammer Hose Assembly ordered separately.

| # Part Number | Individual Carton Dimensions (in) | Approx Wt (lbs/kit) | Approx Wt (kg/kit) | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|-----------------------------------|---------------------|--------------------|-----------------|-------------------|----------|
| 7084JHT75-KIT | 10" x 10" x 3" | 4 | 1.35 | * | 3 | Carton |

Packaging: 3 individually boxed kits per master carton. No broken package shipments.

WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Factory Assemblies Jackhammer Hose

Series 7081 (Red EPDM)



| # Part Number | ID (in) | ID (mm) | Length (ft) | Length (m) | Approx Wt (lbs/ea) | Approx Wt (kg/ea) | Max WP (psi)* | Max WP (bar)* | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|---------|---------|-------------|------------|--------------------|-------------------|---------------|---------------|-----------------|-------------------|----------|
| 7081JHE75-600 | 3/4 | 19.1 | 50 | 15.24 | 16.84 | 7.64 | 200 | 14 | * | 1 | Carton |
| 7081JHE75-600B | | | | | | | | | * | 36 | Carton |

* **NOTE:** Air hose is rated to 200 psi maximum working pressure. Finished hose assembly is rated to 150 psi due to limitation of the industry preferred fitting end.

WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Temp Range: -40°F to +212°F (-40°C to +100°C)

Crimped-on Universal Couplings Each End

Cartoned and Tied: No Center Disc

Sledgehammer Hose

Series 7082 (Red EPDM) and
Series 7083 (Yellow EPDM)



Series 7082 (Red)

| # Part Number | ID (in) | ID (mm) | Length (ft) | Length (m) | Approx Wt (lbs/ea) | Approx Wt (kg/ea) | Max WP (psi)* | Max WP (bar)* | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|---------|---------|-------------|------------|--------------------|-------------------|---------------|---------------|-----------------|-------------------|----------|
| 7082JHP75-600 | 3/4 | 19.1 | 50 | 15.24 | 19.15 | 8.69 | 300 | 21 | * | 1 | Carton |
| 7082JHP75-600B | | | | | | | | | * | 36 | Carton |

Temp Range: -40°F to +212°F (-40°C to +100°C)

Crimped-on Universal Couplings Each End

Cartoned and Tied: No Center Disc



Series 7083 (Yellow)

| # Part Number | ID (in) | ID (mm) | Length (ft) | Length (m) | Approx Wt (lbs/ea) | Approx Wt (kg/ea) | Max WP (psi)* | Max WP (bar)* | Perm Cplg Rec * | Std Pack Qty (ea) | Pkg Type |
|------------------|---------|---------|-------------|------------|--------------------|-------------------|---------------|---------------|-----------------|-------------------|----------|
| 7083JHP75-600 | 3/4 | 19.1 | 50 | 15.24 | 19.23 | 8.72 | 300 | 21 | * | 1 | Carton |
| 7083JHP75-600B | | | | | | | | | * | 36 | Carton |

* **NOTE:** Air hose is rated to 300 psi maximum working pressure. Finished hose assembly is rated to 150 psi due to limitation of the industry preferred fitting end.

WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Temp Range: -40°F to +212°F (-40°C to +100°C)

Crimped-on Universal Couplings Each End










Cartoned and Tied: No Center Disc

Reinforced Conduit Hose

Series 7337



Series 7337 is a durable cable cover with a rugged, abrasion resistant construction that is ideal for extreme service conditions in mining application. Meets MSHA requirements for flame resistance and wall thickness.

| # Part Number |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Nom Std Pack Qty (ft) |  Pkg Type |
|------------------|---|---|--|---|---|--|--|---|--|
| 7337-1382 | 1-3/8 | 34.9 | 2 | 1.8 | 46.0 | 0.68 | 1.01 | 50 | Coil |
| 7337-1502 | 1-1/2 | 38.1 | 2 | 1.9 | 49.0 | 0.72 | 1.07 | 50 | Coil |
| 7337-1752 | 1-3/4 | 44.5 | 2 | 2.2 | 55.4 | 0.83 | 1.24 | 50 | Coil |
| 7337-1882 | 1-7/8 | 47.6 | 2 | 2.3 | 58.6 | 0.88 | 1.31 | 50 | Coil |
| 7337-2002 | 2 | 50.8 | 2 | 2.4 | 61.8 | 0.94 | 1.40 | 50 | Coil |
| 7337-2252 | 2-1/4 | 57.2 | 2 | 2.7 | 68.2 | 1.05 | 1.56 | 50 | Coil |
| 7337-2382 | 2-3/8 | 60.3 | 2 | 2.8 | 71.3 | 1.10 | 1.64 | 50 | Coil |
| 7337-2502 | 2-1/2 | 63.5 | 2 | 2.9 | 74.5 | 1.15 | 1.71 | 50 | Coil |
| 7337-3002 | 3 | 76.2 | 2 | 3.4 | 87.2 | 1.37 | 2.04 | 50 | Coil |
| 7337-3502 | 3-1/2 | 90.0 | 2 | 4.0 | 101.0 | 1.59 | 2.37 | 50 | Coil |
| 7337-4002 | 4 | 102.0 | 2 | 4.4 | 113.0 | 1.79 | 2.67 | 50 | Coil |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black synthetic rubber

Reinforcement: Multiple textile plies

Cover: Black synthetic rubber; wrapped finish

Temp. Range: -30°F to +180°F (-34°C to +82°C)

Brand Method: Embossed

Brand Example: PARKER SERIES 7337 PREMIUM
CONDUIT HOSE FLAME RESISTANT
MINE CONDUIT USMSHA

Industry Standards: MSHA

Applications:

- Conduit
- Underground mining equipment








Vacuum: Not recommended

Reinforced Conduit Hose

Series 7337M



Series 7337M is a durable, smooth finish cable cover with a rugged, abrasion resistant construction that is ideal for extreme service in mining applications, and meets MSHA requirements for flame resistance and wall thickness.

| # Part Number |  ID (in) |  ID (mm) |  Reinf Layers |  OD (in) |  OD (mm) |  Approx Wt (lbs/ft) |  Approx Wt (kg/m) |  Nom Std Pack Qty (ft) |  Pkg Type |
|------------------|--|--|---|--|--|--|---|--|---|
| 7337M-502 | 1/2 | 12.7 | 2 | 1.0 | 24.6 | 0.31 | 0.46 | 450 | Reel |
| 7337M-502050 | | | | | | | | 50 | Carton |
| 7337M-632 | 5/8 | 15.9 | 2 | 1.1 | 27.8 | 0.37 | 0.55 | 400 | Reel |
| 7337M-632050 | | | | | | | | 50 | Carton |
| 7337M-752 | 3/4 | 19.1 | 2 | 1.2 | 30.8 | 0.41 | 0.61 | 350 | Reel |
| 7337M-752050 | | | | | | | | 50 | Carton |
| 7337M-1002 | 1 | 25.4 | 2 | 1.5 | 37.2 | 0.52 | 0.77 | 250 | Reel |
| 7337M-1002050 | | | | | | | | 50 | Carton |
| 7337M-1132 | 1-1/8 | 28.6 | 2 | 1.6 | 40.5 | 0.57 | 0.85 | 250 | Reel |
| 7337M-1132050 | | | | | | | | 50 | Carton |
| 7337M-1252 | 1-1/4 | 31.8 | 2 | 1.7 | 43.6 | 0.63 | 0.94 | 250 | Reel |
| 7337M-1252050 | | | | | | | | 50 | Carton |

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Tube: Black synthetic rubber

Reinforcement: Multiple textile plies

Cover: Black synthetic rubber; smooth finish

Temp. Range: -30°F to +180°F (-34°C to +82°C)

Brand Method: Impression (2-sided)

Brand Example: Side 1: PARKER 7337M PREMIUM MINE
CONDUIT HOSE FLAME RESISTANT
USMSHA
Side 2: (ID) USMSHA

Industry Standards: MSHA

Applications:

- Conduit
- Underground mining equipment

Vacuum: Not recommended